




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B65D 47/18	A1	(11) International Publication Number: WO 99/57030 (43) International Publication Date: 11 November 1999 (11.11.99)
(21) International Application Number: PCT/US99/09749 (22) International Filing Date: 4 May 1999 (04.05.99) (30) Priority Data: 09/072,245 4 May 1998 (04.05.98) US (71) Applicant: DENTSPLY INTERNATIONAL INC. [US/US]; 570 West College Avenue, P.O. Box 872, York, PA 17404-0872 (US). (72) Inventor: WILNER, Ralf; Untere Schlosshalde 7, D-78351 Bodman-Ludwigshafen (DE). (74) Agents: HURA, Douglas, J. et al.; Dentsply International Inc., 570 West College Avenue, P.O. Box 872, York, PA 17404-0872 (US).	(81) Designated States: JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.	

(54) Title: DENTAL ADHESIVE CONTAINER DROPPING SYSTEM

(57) Abstract

Dental adhesive container dropping system, characterized by the combination of: (a) a dental adhesive polymerizable with visible light dissolved in acetone or acetic acid ethyl ester; (b) a light impermeable bottle (1) for the dental adhesive, elastically deformable for the drop formation, with a laminated wall (3) comprising (b1) at least one polymer layer (15) impermeable to acetone or acetic acid ethyl ester, and (b2) at least one light impermeable, elastically deformable polymer layer (13); (b3) a compatibilizer guaranteeing the laminate structure and which can be formed as at least one intermediate layer (17) or which can be admixed to the elastically deformable polymer layer (13); (c) a light impermeable and evaporation-proof sealable dropper insert (20) of light impermeable plastic material with a dropper conduit (50) enlarging from the inner to the outer part; whereby (c1) the diameter at the inlet end corresponds to the desired drop size and (c2) the diameter at the discharge end is within the range of from 0.1 to 0.25 mm.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

DENTAL ADHESIVE CONTAINER DROPPING SYSTEM

The invention relates to a system of a polymerizable dental adhesive, a bottle and a dropper.

In a known system of this kind, the dental adhesive is polymerizable with visible light and contains acetone as a solvent. In order to avoid a loss of acetone, a light impermeable glass bottle had to be used as a container. However, this requires the use of a gravitation dropper with a ventilation hole. As a consequence, the dropping frequency is very high and cannot be controlled because of the low viscosity of acetone used as a solvent. After the application of the first desired drop, the user has to turn around the bottle very quickly, before the next undesired drop can flow out. In practice, this causes great difficulties.

Furthermore, it has already been known to use a plastic bottle for a dental adhesive on acetone basis as well as a dropper insert with a single dropper conduit. There is a considerable loss by acetone diffusion through the bottle wall. For a delimitation of this problem to a certain extent, the bottle wall must be very thick and/or consist of a material which is slightly more diffusion proof and therefore stiffer. Consequently, manual compression of the bottle for controlling the drop formation is difficult. For this reason, a dropper conduit of at least 0.3 mm is provided which has a relatively great lumen. However, this has serious disadvantages. Firstly, the liquid runs out under the mere affect of gravitation. Secondly, the drop frequency cannot be manually controlled. Notably, a second undesired drop can hardly be avoided. Thirdly, the dropper conduit having a great lumen causes the problem of an undesired

light incidence. Furthermore, a residual amount of dental adhesive in the bottle with the great wall thickness can be recognized by the shaking sound only with difficulties.

It is therefore the problem of the invention to provide a dental adhesive container dropping system wherein on the one hand the dental adhesive polymerizable with visible light may contain acetone as a solvent and wherein on the other hand the drop formation is manually controllable, the running out of further undesired drops is avoidable, and yet the loss by acetone diffusion is avoided to a great extent.

This problem is solved by the dental adhesive container drop system according to Claim 1. Preferred embodiments are indicated in the subclaims.

In the following, the invention is explained in detail by means of Figures.

Figure 1 shows a cross-section of a bottle with dropper insert of the system according to the invention

Figure 2 shows an enlarged cross-section of the dropper insert according to Figure 1; and

Figure 3 shows a cap for the bottle according to Figure 1.

Figure 1 shows a bottle 1 with a cylindrical wall 3, a bottom 5, a shoulder portion 7 and a neck portion 9 with an outer winding 11. A part of the cross-section of the cylindrical wall is enlarged, whereby the laminate structure is shown. An outer wall 13 consists of a light impermeable coloured polyolefin and is self-supporting and elastic. An inner layer 15 consists of a material which is effective as a barrier material against the permeation of acetone vapor. The intermediate layer 17 of compatibilizer guarantees a solid adhesion of the laminate. The bottom 5 and the shoulder portion 7 have the same structure.

Polymers for the outer wall 13 are preferably polyolefines such as polyethylene, polypropylene, polybutylene or polycarbonate. Preferred is polyethylene having a low density (LDPE) or a polyolefine mixture having a content of at least 50% by weight LDPE or a polymer having at least the same elasticity.

Materials for the inner layer 15 are preferably polyamides, polyepoxides, polyesters, polyvinyl alcohol or copolymers or mixtures thereof. Amorphous polyamides such as 6,6-nylon, 6,9-nylon, 6,10-nylon, 6,12-nylon, polycaprolactam are especially suitable as polyamides. Polyglycidylethers of aromatic polyols such as bisphenol A or the like or aliphatic polyols such as 1,2-ethanediol, 1,2-propanediol, 1,3-propanediol, 1,4butanediol, diethylene glycol, triethylene glycol are especially suitable as polyepoxides. The molecular weight of the polyamides is preferably at least 5,000. The molecular weight of the polyepoxides is at least 2000.

A polyolefine of the above-mentioned nature with polymerized units with carboxylic acid groups, carboxylic acid amide groups or carboxylic acid ester groups is especially suitable as an intermediate layer.

Alternatively, the layer of the above-mentioned nature being effective as a barrier material against acetone vapor can also be provided as an intermediate layer and can be laminated on both sides with identical layers of a mixture of polyolefine and the compatibilizer of the above-mentioned nature.

Preferably, the bottle has an inner volume of from 3 to 10 ml, preferably from 5 to 9 ml. The average wall thickness in the cylindrical portion is preferably from 0.3 to 1.5 mm, specifically from 0.5 to 1 mm and notably from 0.7 to 1 mm.

A one-piece dropper insert 20 of light impermeable polypropylene is inserted into the neck portion 9 of the bottle 1. This dropper insert comprises an insert body 22 with a convex outer surface 24 and an inner surface 26 conically enlarging to the bottom. The insert body is completely inserted into the neck portion 9 of the bottle 1 - With the arcuate outer surface 24 it snaps into a correspondingly concave-shaped arcuate inner surface of the neck portion 9 of the bottle 1. Hereby, an increased density against acetone vapor is obtained. A radial flange 28 follows the body 24 at the upper part. Said flange 28 is positioned with a lower surface 30 on the upper rim of the neck portion 9 of the bottle 1. An upper surface 32 of the flange is effective as a closing surface for a below-described stopper. At the upper part, a flange 28 is followed by a nozzle body 34 which has a cylindrical lower outer surface 36 and an upper surface 38 which is truncated-cone-shaped. An inner cylindrical surface 40 extends up to the conical portion. A further truncated-cone-shaped portion 42 extends in the inner part of the nozzle body downwards. The nozzle body 34 has an upper border by a laminated surface 44, and the portion 42 has a lower border by a laminated surface 46. A dropper conduit 50 extends from the laminated surface 44 to the laminated surface 46. The dropper conduit 50 has an upper cylindrical portion 52 and a lower portion 54 conically enlarging from the bottom to the top. The length C of the dropper conduit 50 is preferably 3 to 18 mm, notably from 4 to 10 mm and especially from 5 to 8 mm. The diameter B at the discharge end of the dropper conduit 50 is preferably 0.8 to 2.5 mm, notably 1.0 to 2.0 mm and especially 1.2 to 1.6 mm. It determines the desired size of the drops formed. The smallest diameter A of the inlet end of the dropper conduit 50 is 0.1 to 0.25 mm, preferably 0.1 to 0.15 mm and especially 0.12 to 0.14 mm. It determines the passage rate of the dental adhesive.

A cap 60 cross-sectionally shown in Figure 3 of black polypropylene shows an inner winding 62. An inner projection 64 with an upper cylindrical portion 66 and a lower conical portion 68 engages in a sealing manner into dropper conduit 50. Further, a torus 70 is provided, which interacts in a sealing manner with the upper surface 32 of the flange 28.

Claims:

- 1 Dental adhesive container dropping system, characterized by the combination of
 - (a) a dental adhesive polymerizable with visible light dissolved in acetone or acetic acid ethyl ester,
 - (b) a light impermeable bottle (1) for the dental adhesive, elastically deformable for the drop formation, with a laminated wall (3) comprising (b1) at least one polymer layer (15) impermeable to acetone or acetic acid ethyl ester, and
 - (b2) at least one light impermeable, elastically deformable polymer layer (13),
 - (b3) a compatibilizer guaranteeing the laminate structure and which can be formed as at least one intermediate layer (17) or which can be admixed to the elastically deformable polymer layer (13),
 - (c) a light impermeable and evaporation-proof sealable dropper insert (20) of light impermeable plastic material with a dropper conduit (50) enlarging from the inner to the outer part, whereby
 - (c1) the diameter at the inlet end corresponds to the desired drop size and
 - (c2) the diameter at the discharge end is within the range of from 0.1 to 0.25 MM.
2. Dental adhesive container dropping system according to Claim 1, characterized in that the bottle has an inner volume of from 3 to 10 ml.
3. Dental adhesive container dropping system according to one of Claims 1 or 2, characterized in that the bottle (1) has a wall thickness of from 0.3 to 1.5 mm.

4. Dental adhesive container dropping system according to one of Claims 1 to 3, characterized in that the dropper insert (20) comprises a dropper conduit (50) having a diameter at the discharge end of from 0.8 to 2.5 mm.
5. Dental adhesive container dropping system according to one of Claims 1 to 4, characterized in that the dropper insert (20) comprises a dropper conduit (50) having a length of from 3 to 18 mm.
6. Dental adhesive container dropping system according to one of Claims 1 to 5, characterized in that the dropper insert (20) is inserted into the neck portion (9) of the bottle (1) with a barrel-shaped arcuate insert body (22).
7. Dental adhesive container dropping system according to one of Claims 1 to 6, characterized in that the dropper insert (20) has a dropper conduit (50) with dimensions that, when the bottle has been turned around and the bottom has been removed, the drop frequency under the influence of gravitation at ambient temperature is 3-50 drops per minute, preferably 5 to 20 drops per minute.
8. Dental adhesive container dropping system according to one of Claims 1 to 7, characterized in that the bottle (1) can be sealed with a screw cap (60) which engages the discharge end of the dropper conduit (50) with a pin-shaped inner projection (64).
9. Dental adhesive container dropping system according to one of Claims 1 to 8, characterized in that the bottle (1) can be sealed with a screw cap (60) which lies with a torus (70) on a flange surface (32) of the dropper insert.

10. Dental adhesive container dropping system according to one of Claims 1 to 8, characterized in that the bottle (1) has an approximately cylindrical shape.

Fig. 1




Fig. 2





Fig. 3



INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/09749

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 B65D47/18

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B65D B32B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 081 164 A (LAI JUEY H) 14 January 1992 (1992-01-14) column 7, line 3-8 column 11, line 58-61 ---	1-10
A	US 4 498 609 A (STOCK HUGH J) 12 February 1985 (1985-02-12) column 2, line 8-22 figures 1,2 ---	1-10
A	EP 0 431 885 A (MERCK SHARP & DOHME) 12 June 1991 (1991-06-12) ---	
P, X	DE 197 13 951 A (DENTSPLY DETREY GMBH) 8 October 1998 (1998-10-08) the whole document --- -/--	1-10

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

18 August 1999

Date of mailing of the international search report

25/08/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Chabus, H

INTERNATIONAL SEARCH REPORT

Inter national Application No
PCT/US 99/09749

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, A	<p>WO 98 31742 A (DENTSPLY INT INC) 23 July 1998 (1998-07-23) page 3, line 22 - page 4, line 10 page 11, line 14-21 -----</p>	1-10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/09749

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5081164 A	14-01-1992	NONE	
US 4498609 A	12-02-1985	DE 3028079 A FR 2470064 A GB 2059401 A JP 56057652 A	02-04-1981 29-05-1981 23-04-1981 20-05-1981
EP 0431885 A	12-06-1991	FR 2655623 A CA 2031632 A JP 3251249 A	14-06-1991 09-06-1991 08-11-1991
DE 19713951 A	08-10-1998	NONE	
WO 9831742 A	23-07-1998	NONE	